Copy for the Elected Office (EO/US)

PATENT COOPERATION TREATY

	From the INTERNATIONAL BUREAU
PCT	То:
NOTIFICATION OF THE RECORDING OF A CHANGE (PCT Rule 92bis.1 and Administrative Instructions, Section 422) Date of mailing (day/month/year) 21 December 2000 (21.12.00)	SURESAN, Sachithananthan C/O Tan Rajah & Cheah 9 Battery Road, #15-00 Straits Trading Building Singapore 049910 SINGAPOUR
	<u> </u>
Applicant's or agent's file reference PAP120-PCT	IMPORTANT NOTIFICATION
International application No.	International filing date (day/month/year)
PCT/SG99/00117	10 November 1999 (10.11.99)
The following indications appeared on record concerning: the applicant	the agent the common representative State of Nationality State of Residence
APPLIED RESEARCH CORPORATION Kent Ridge P.O. Box 1016 Singapore 911101 Singapore	Telephone No. 65-7755822
Singapore	Facsimile No. 65-7730924
	Teleprinter No.
2. The International Bureau hereby notifies the applicant that the	ne following change has been recorded concerning:
X the person X the name X the add	fress the nationality the residence
Name and Address	State of Nationality State of Residence
SURESAN, Sachithananthan C/O Tan Rajah & Cheah 9 Battery Road, #15-00	Telephone No.
Straits Trading Building Singapore 049910 Singapore	Facsimile No.
	Teleprinter No.
3. Further observations, if necessary:	
4. A copy of this notification has been sent to:	
X the receiving Office	the designated Offices concerned
the International Searching Authority	X the elected Offices concerned
X the International Preliminary Examining Authority	other:
The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland	Authorized officer Christine Carrié Telephone No.: (41, 23), 238, 93, 28

PATENT COOPERATION TREATMY

	From the INTERNATIONAL BUREAU
PCT	То:
NOTIFICATION OF ELECTION (PCT Rule 61.2)	Assistant Commissioner for Patents United States Patent and Trademark Office Box PCT Washington, D.C.20231 ETATS-UNIS D'AMERIQUE
Date of mailing (day/month/year)	in its capacity as elected Office
30 June 2000 (30.06.00)	
International application No. PCT/SG99/00117	Applicant's or agent's file reference PAP120-PCT
International filing date (day/month/year)	Priority date (day/month/year)
10 November 1999 (10.11.99)	12 November 1998 (12.11.98)
Applicant	
LI, Sam, Fong, Yao et al	
The designated Office is hereby notified of its election made in the demand filed with the International Preliminary 07 April 2000 in a notice effecting later election filed with the International Preliminary 2. The election was was not made before the expiration of 19 months from the priority Rule 32.2(b).	y Examining Authority on: (07.04.00) national Bureau on:
The International Bureau of WIPO 34, chemin des Colombettes	Authorized officer
1211 Geneva 20, Switzerland	S. Mafla
Facsimile No.: (41-22) 740.14.35	Telephone No.: (41-22) 338.83.38

50 50 CO

PATENT COOPERATION TREATY

PCT

	REC'D	0	1	МДҮ	2001	
L	WIPO		_	F	CT	

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

2

Applicant's or agent's file reference PAP120-PCT	FOR FURTHER ACTION	N See Notif	ication of Transmittal of International Preliminary
	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		ion Report (Form PCT/IPEA/416)
International application No.	International filing date (day/mo	• •	Priority Date (day/month/year)
PCT/SG 99/00117	10 November 1999 (10).11.1999)	12 November 1998 (12.11.1998)
International Patent Classification (IPC) or nat	ional classification and IPC		
IPC ⁷ :			
Applicant			
NATIONAL UNIVERSITY OF SIN	GAPORE et al.		
This international preliminary example and is transmitted to the applicant.		pared by this Ir	aternational Preliminary Examination Authority
2. This REPORT consists of a total o	f 3 sheets, includi	ng this cover	sheet.
amended and are the basis f		ontaining recti	ription, claims and/or drawings which have been fications made before this Authority (see Rule Γ).
These annexes consist of a total of	sheets.		
3. This report contains indications rela	ating to the following items:		
I. Basis of the opini	ion		
II. Priority			1
III. Non-establishmen	nt of opinion with regard to n	ovelty, invent	ive step and industrial applicability
IV. Lack of unity of i	invention		
	ent under Rule 66.2(a)(ii) with lanations supporting such sta		velty, inventive step or industrial applicability;
VI. Certain document	ts cited		
VII. Cestain defects in	the international application		
VIII. Certain observati	ons on the international appli	cation	•
Date of submission of the demand	Dat	te of completio	on of this report
]		
7 April 2000 (07.04	l.2000)	11 De	cember 2000 (11.12.2000)
Name and mailing address of the IPEA/A	T Aut	thorized office	r
Austrian Patent Office Kohlmarkt 8-10			TENGLER
A-1014 Vienna			LINOLLIN
Facsimile No. 1/53424/200	Tel	ephone No. 1.	/53424/213

Form PCT/IPEA/409 (cover sheet) (July 1998)

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.	
PCT/SG 99/00117	

<u>L</u>	Wit	Basis of the report h regard to the elements of the international application:*
	\boxtimes	the international application as originally filed
		the description: pages, as originally filed pages, filed with the demand pages, filed with the letter of
		the claims: pages, as originally filed pages, as amended (together with any statement) under Article 19 pages, filed with the demand pages, filed with the letter of
		the drawings: pages, as originally filed pages, filed with the demand pages, filed with the letter of
		the sequence listing part of the description: pages, as originally filed pages, filed with the demand pages, filed with the letter of
2.	whi	h regard to the language, all the elements marked above were available or furnished to this Authority in the language in ch the international application was filed, unless otherwise indicated under this item. se elements were available or furnished to this Authority in the following language which is:
		the language of a translation furnished for the purposes of international search (under Rule 23.1(b)).
		the language of publication of the international application (under Rule 48.3(b)).
		the language of the translation furnished for the purposes of international preliminary examination (under Rule 55.2 and/ or 55.3).
3.		h regard to any nucleotide and/or amino acid sequence disclosed in the international application, the international iminary examination was carried out on the basis of the sequence listing:
		contained in the international application in printed form.
		filed together with the international application in computer readable form.
		furnished subsequently to this Authority in written form.
		furnished subsequently to this Authority in computer readable form.
		The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
		The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.
4.		The amendments have resulted in the cancellation of:
		the description, pages
		the claims, Nos
		the drawings, sheets/fig
5.		This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).**
i	n this	cement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and
	(0.17) Iny re	eplacement sheet containing such amendments must be referred to under item 1 and annexed to this report.

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/SG 99/00117


V. Reasoned statement under Ar- citations and explanations sup		with regard to novelty, inventive step or industrial applicability; uch statement	
1. Statement			
Novelty (N)	Claims	1-22	YES
	Claims		NO
Inventive step (IS)	Claims	1-22	YES
	Claims		NO
Industrial applicability (IA)	Claims	1-22	YES
	Claims		NO
Citations and explanations (Rule 70	.7)		

The following documents D1-D4 as given in the International Search Report are referred to in this communication. The numbering will be adhered to in the rest of the procedure:

WO 98/51393 A1 (D1); GB 2 336 908 A (D2); DE 197 39 120 A1 (D3); US 5,702,672 A (D4)

As already indicated in the International Search Report, none of the cited documents D1-D5 (from which D1-D3 have been published prior to the filing date of the present application but later than the priority date claimed) discloses all essential and characteristic features of the device and method for the concentration of samples by microcrystallization which are the subject matters of the present application. Therefore, the present application is considered to meet the requirement of novelty.

The device according to the present application has a first thermostat (12) in the top of which are wells (40) containing samples. A second thermostat (11) has wires (20) adapted to be inserted into samples in the wells. An insulator (30) insulates the two thermostats from each other such that heat from the samples is dissipated through the wires. The device can be used for the concentration of small volume samples, e.g. in drug development and has the advantage, that analytes can be concentrated in small volumes and in large numbers. Since neither such a device nor its advantageous use for the microcrystallization of samples is suggested from prior art teachings, the present application appears to meet the requirement of inventive step, as well.



Industrial applicability of the subject matter of the present application is obviously given.





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 00/29102 (51) International Patent Classification 7: (11) International Publication Number: A1 B01J 9/04 25 May 2000 (25.05.00) (43) International Publication Date:

SG

PCT/SG99/00117 (21) International Application Number:

10 November 1999 (10.11.99) (22) International Filing Date:

12 November 1998 (12.11.98)

(71) Applicant (for all designated States except US): NATIONAL

UNIVERSITY OF SINGAPORE [SG/SG]; Industry & Technology Relations Office (INTRO), 10 Kent Ridge Crescent, Singapore 119260 (SG).

(72) Inventors; and (75) Inventors/Applicants (for US only): LI, Sam, Fong, Yao [SG/SG]; INTRO, National University of Singapore, 10 Kent Ridge Crescent, Singapore 119260 (SG). WEI, Hongping [CN/SG]; INTRO, National University of Singapore, 10 Kent Ridge Crescent, Singapore 119260 (SG).

(74) Agent: APPLIED RESEARCH CORPORATION; Kent Ridge, P.O. Box 1016, Singapore 911101 (SG).

(81) Designated States: US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT,

Published

With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: DEVICE AND METHOD FOR CONCENTRATION OF SAMPLES BY MICROCRYSTALLIZATION


(57) Abstract

ķ

(30) Priority Data:

9804033-0

A device and method for simultaneously concentrating a plurality of samples in small volumes based on the principle of crystallization. The device comprises a device for concentrating a plurality of samples comprising: a first temperature control means (12) having a plurality of container means (40/50) for containing said plurality of samples; a second complementary temperature control means (11) having a plurality of conducting means (22) which are adapted to be inserted in respective samples in said plurality of container means (40/50); and insulating means (30) for insulating said first temperature control means (12) from said temperature control means (11) such than an amount of heat from said plurality of samples is dissipated through said plurality of conducting means (22).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	ΙE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JР	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	КZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

WO 00/29102 PCT/SG99/00117

Device and Method for Concentration of Samples by Microcrystallization

Background of the invention

1. Field of the invention

The present invention relates generally to the field of sample handling and to sample preconcentration. More particularly, this invention relates to a method and device for concentration of samples, such as analyte solutions, on the principle of crystallization.

2. Description of the prior art.

10

15

20

In order to meet the requirement of current environmental, biochemical and clinical analysis, where more information is needed to be drawn from a small amount of samples, such as blood or a solution containing quite small amount of interesting compounds, suitable devices and methods need to be developed for handling and concentrating these samples. The most widely used methods currently are based on extraction, such as solid phase extraction, solid phase microextraction, and liquid – liquid extraction. There are also other methods which could be used, such as evaporation. There is hardly any method for concentrating sample solutions based on the principle of crystallization.

When a crystalline phase is formed from a fluid phase, the process is commonly called crystallization. Due to the high selectivity by which atoms, ions, and molecules may be built in a crystal lattice, crystallization has been used in industry for producing high purity compounds. With the selected compounds (usually the major component in the liquids, such as water in aqueous solutions and organic solvents in organic solutions) crystallizing out from the liquid and becoming purified, the other compounds (usually the minor components in the liquid, or analytes when they are the compounds of interest) become concentrated in the remaining liquid. Freeze concentration is a process for concentrating aqueous solutions by removing water in the form of ice. Using crystallization to concentrate samples can provide several advantages over other concentration techniques often used in analytical chemistry, such as extraction and evaporation. Compared with methods of extraction, no organic solvent or any other reagents are needed during crystallization, which will reduce the danger of contamination to samples and the cost for

disposing toxic reagents. Compared with evaporation, crystallization can be used to concentrate semi-volatile and volatile samples. In addition, crystallization can concentrate analytes in solid samples which can be changed into liquid state under certain conditions, such as heating them to a certain temperature. Few concentration techniques in current analytical chemistry can concentrate solid samples directly. Until now, there are only a few papers available which address concentration and analysis of organic solvents and anions in aqueous solution based on freeze concentration. The process of freeze concentration is usually quite long, generally several hours, and generally requires large sample solutions (at least several mL).

Recently, with the intense pharmaceutical drug discovery efforts, combinatorial chemistry is offering great challenges to analytical chemistry. Combinatorial chemistry is a style of synthesis in which selected building blocks are combined in different ways so as to produce large numbers, or libraries, of new molecular variants much more efficiently than is possible by traditional synthetic approaches (Chem. Rev., March 1997). It has given drug discovery units in pharmaceutical companies a crank with a very long handle, producing in a few days a 50,000 – compound library of new molecular structures. Subsequently compounds showing activity of the kind sought and their structures will need determining. In addition, most combinatorial methodologies yield only 0.1 to micromole quantities of product, which are localized on polymer beads, plastic "pins", or in microtiter plate wells. Thus, very high analytical sensitivities are demanded. The method described in the present invention which can concentrate analytes in small volumes and concentrate hundred or thousand of them simultaneously could be very useful and highly desirable.

Summary of this invention

10

15

20

25

The present invention is directed to a method and device which can simultaneously concentrate a plurality of samples in small volumes based on the principle of crystallization.

In one embodiment, there is provided a device for concentrating a plurality of samples comprising:

a first temperature control means having a plurality of container means for containing said plurality of samples;

a second complimentary temperature control means having a plurality of conducting means which are adapted to be inserted in respective samples in said plurality of container means; and

insulating means for insulating said first temperature control means from said second temperature control means such that an amount of heat from said plurality of samples is dissipated through said plurality of conducting means.

5

10

15

20

25

30

According to another embodiment there is provided a method for concentrating a plurality of samples comprising:

placing a plurality of samples in a first temperature control means having a plurality of container means for containing said plurality of samples;

inserting a conducting means into each of said samples, said conducting means being mounted relative to a second complimentary temperature control means;

cooling said plurality of samples by means of said first and second temperature control means to selectively crystallize components of said samples; and

removing said crystallized components from said samples.

The first and second temperature control means may include any suitable means for controlling the temperature of the plurality of samples. In a preferred embodiment, the first and second temperature control means comprise first and second cooling means. More preferably, each of the first cooling means and second cooling means comprises thermostat controlled cooling means for providing a constant temperature, a stable variable temperature, a temperature gradient, or a series of temperature gradients. In certain embodiments, the first and second temperature control means are individually selected from circulating heaters and coolers, heating and cooling blocks and slush baths.

In a preferred embodiment, the plurality of container means are located in a face of the first temperature control means, and the insulating means comprises a layer of insulating material disposed on a face of the second temperature control means opposing the face of the first temperature control means on which the plurality of container means are located. Most preferably, the plurality of conducting means passes from the second temperature control means through the insulating material and, in use, into the plurality of samples in the plurality of container means.

The insulating means preferably partly or completely prevents transfer of heat between the first temperature control means and the second temperature control means. In a particularly preferred embodiment, the insulating means comprises a plastic foam insulator.

5

10

15

20

25

30

The conducting means may comprise any suitable conducting material, and may be of any suitable form which facilitates the conduction of heat from the sample through the conducting means. Preferably, the plurality of conducting means comprises a plurality of wires. The wires may be formed from metal, polymer, inorganic or organic material, and preferably comprise copper wires, each wire optionally comprising an outer protective layer. Furthermore, each of the wires may include a single wire, or may include a plurality of wires. Preferably, each of said wires has a diameter of from about several nanometers to several centimeters. More preferably, each of the wires has a diameter of about 1 millimeter.

The container means may comprise any suitable means for containing the plurality of samples. In a preferred embodiment, the container means comprises a plurality of wells, each of which receives one of the plurality of samples or is adapted to receive a sample container holding one of the plurality of samples. In this regard, the samples may be introduced directly into the wells, or may be placed into sample containers which are in turn placed in the wells. In the latter case, it is preferred that each sample container comprises a tube, bottle or vial. In a particular embodiment, the sample container comprises a dialysis tube.

Once the samples are in place, the first and second temperature control means are generally moved from a loading position to an operative position in which the conducting means are inserted into respective samples. This may be achieved either manually or automatically as desired.

In use, the conducting means, having been inserted in respective samples, and advantageously act as a support for nucleation during the crystallization. Further, in a preferred embodiment, as the crystallized components are crystallized on the conducting means acting as a support, the conducting means advantageously facilitates removal of the crystallized components from the container means.

The crystallization of components of the samples will, as will be readily understood by a person skilled in the art, be carried out at a temperature which is dependent on the characteristics of the samples, and the desired final concentrate. However, the crystallization will generally be carried out at a temperature of from - 70°C to about 0°C.

As will be understood by a person skilled in the art, the samples may take any suitable form. In particular, the present invention may be used to concentrate various aqueous solutions, organic solutions, or solids which can be liquefied under certain conditions, for example at elevated temperature.

The solutions remaining in the sample containers are concentrated solutions which may be used for further analysis by other analytical instruments. Another cycle of concentration may also be carried out after the crystals on the wires are removed by heating or other methods.

While those skilled in art will recognize that there exists a multitude of applications relevant to the present invention, the invention will now be described in the context of the analysis of aqueous samples by freeze concentration, a particularly suitable application of the present invention.

Additional features, aspects and advantages of certain embodiments of the invention will be more fully understood when considered in connection with the accompanying drawings and the detailed description which follows.

20 Brief description of the drawing

5

10

15

- Fig. 1 is a schematic diagram of the device of the present invention for concentration of a plurality of sample solutions simultaneously by microcrystallization. Only 3 x 6 array is shown for demonstration. The real device can be as much as 100 x 100 or more.
- Fig. 2 is a schematic diagram of partial section view taken along one row of the sample containers when the device in fig.1 is in operation.
 - Figs. 3A to 3D illustrates the process of ice growth and separation from the concentrated solutions during freeze concentration, taking one sample container as an

example.

5

Fig. 4 is the typical electropherograms, obtained by capillary electrophoresis, of five kinds of inorganic anions before and after applying the freeze concentration process of the present invention.

Fig. 5 is the typical electropherograms, obtained by capillary electrophoresis, of two phenols before and after applying the freeze concentration process of the present invention.

Fig. 6 is the typical electropherograms, obtained by capillary electrophoresis, of two proteins before and after applying the freeze concentration process of the present invention.

Figs. 7A and 7B are the chromatographs, obtained by gas chromatography, of organic solvents in wastewater before and after applying the freeze concentration process of the present invention.

The term "thermostat" as used hereafter refers to a temperature regulated cooling device.

Detailed Description of a preferred embodiment

Referring to Figure 1, a device for carrying out microcrystallization has two thermostats 11 and 12 for controlling temperatures, a plurality of wires 20 for conducting heat, a thermal insulator 30 between the thermostats 11 and 12, and a plurality of sample containers 50. Each of the wires 20 has two ends 21 and 22. The wires 20 are immobilized vertically and individually on the bottom of the thermostat 11 in an array so that their ends 21 are located in the thermostat 11 and their ends 22 lie outside the thermostat 11. The wire ends 22 also pass through the thermal insulator 30 which is immobilized on the outside bottom of the thermostat 11. On the top of the thermostat 12, a plurality of wells 40 are created in the same array pattern as that for the wires 20. The size and shape of the wells 40 should match the size and shape of the sample containers 50 so that the sample containers 50 can be put in and taken out easily from the wells 40 and there are little spaces between them when the containers 50 are in the wells 40. If the wells 40 can be removed from the thermostat 12, the well 40 can be sample containers also. The sample containers 50 could

have caps or no caps. In either way, the top of each of the sample containers 50 has a hole or space whose size is larger than any other inner space of the sample containers 50 so that the crystal produced can be removed with the wires 20 from the sample containers 50.

For operating the device of the present invention, sample solutions with known volumes or solid samples with known weights are filled into the sample containers 50 first. Then containers 50 with the samples are put into the wells 40 individually. Finally, the thermostat 11 moves down so that each of the wire ends 22 is inserted into the individual sample containers 50 and immersed into the sample solutions. Fig. 2 illustrates the relative positions of the thermostats 11 and 12, the sample containers 50 and the wires 20 at this stage. The temperature of the thermostat 12 is adjusted to set the temperature of the sample solutions in the sample containers 50, whereas the temperature of the thermostat 11 is adjusted to an appropriate temperature at which the major components in the sample solutions will crystallize out. Time is recorded in order to control the time for the concentration. Finally, when most of the sample solutions in the sample containers 50 attain crystalline state, the thermostat 11 moves up. The crystals produced will be removed, along with the wires 20, from the sample containers 50. The concentrated solutions will remain in the sample containers and can be moved with the sample containers 50 for further analysis. For another cycle of concentration, the crystals outside the wires 20 from the latest process can be removed by heating or other means. After washing the wire ends 22, the same procedure as described above can be used again.

10

15

20

25

30

As discussed above, the thermostats 11 and 12 can be any apparatuses that can control temperature. For example, circulating heater and cooler, heating or cooling blocks, thermoelectric devices, slush baths (low-melting-point liquids kept in a partially frozen state by either liquid nitrogen or dry ice), and many others apparatus known to those skilled in the art. The choice of the thermostats depend on the temperature needed for crystallization. Usually the temperature given by the thermostat 12 should be in the range of temperatures between which the sample will be in liquid state, while the temperature given by the thermostat 11 should be in the range of temperatures between which the major components of the sample will be crystallized out. For example, when aqueous solutions need to be concentrated, the thermostat 11 can be those which can control its temperature below 0 °C because the freezing point of water is 0 °C, and the thermostat 12 can be those which can

control the temperature above 0 °C. The heat produced in the sample containers 50 during formation of ice can be drawn through the wires 20 into the thermostat 11 and be dissipated. In such way, the ice can only form first on the outside of the wire ends 22 and then grow further into the other area of the solution. At the final stage, ice can be easily separated from the concentrated solutions because it will be removed together with the wires 20. If desired, the freeze concentration process may be accelerated by choosing a thermostat 11 which can generate a much lower temperature, for example, - 70 °C, or a thermostat 12 which can generate a temperature quite near 0 °C. It will be seen in the following examples that the growth rate of ice may be controlled in this way.

5

10

15

20

25

30

For purpose of conducting heat and separating the crystal produced, the preferred wires 20 should be those having good thermal conductivity and good mechanic strength. Metal wires, especially copper wires, usually is a good choice. However, other materials, such as polymers, can be used also. The diameter of the wires 20 can range from centimeters to several micrometers, or even to nanometers, depending on the volume or the amount of the sample needed for concentration. For small volumes of samples, thin wires 20 are preferred. Other considerations could be whether the material used will cause contamination or other unwanted effects to the samples because of contact of the wire ends 22 with the samples. For example, copper wire could be a problem for use to concentrate copper ions in aqueous solutions. Sometimes copper ions can cause damage to the activities of some enzymes. In such cases, a thin layer of another material is coated to the copper wires, or copper wires are not used.

The choice of sample containers 50 also depends on the samples needing concentration. For samples with small volumes, small containers are preferred. For some solid samples such as phenols, the material of the sample containers should be able to withstand the temperature used to melt the solid samples. For the purpose of separating the crystal from the concentrated solutions easily, the shape of the containers should preferably have a wide opening and a narrow bottom, like that of centrifuge tubes. In some cases, such as when using mass spectrometry (MS) to determine the structure of proteins, the sample containers can be dialysis tubes, or may contain a dialysis membrane so that the small ions can be removed as inorganic ions are non-volatile and MS is quite sensitive to them.

The thermal insulator 30 can be foam or any other suitable materials. Its purpose is to separate the two thermostats 11 and 12 effectively so that the heat produced is mainly dissipated through the wires 20, and therefore facilitate the control of the growth of crystals.

Besides concentrating aqueous solutions, the present invention can be used to concentrate organic solutions and solids, such as benzene, xylene and phenol.

Those skilled in the art will recognize that the foregoing description provide a method and a device which can concentrate a plurality of samples simultaneously based on crystallization. In the examples which follow, the ability of the present device to concentrate minute amounts of analytes in aqueous solutions is demonstrated.

EXAMPLE 1

5

10

15

20

25

In this experiment the performance of the device of the present invention is demonstrated to concentrate five inorganic anions (Cl⁻, SO_4^{2-} , NO_3^{-} , NO_2^{-} and Br⁻, each at the concentration of 0.1 μ g/mL) in high purity water. A slush bath (prepared by mixing ethanol with dry ice) with a temperature of -70 °C was chosen as the thermostat 11, and a water bath (room temperature 25 °C) was used as the thermostat 12. The copper wires 20 were of diameter 1 mm. Eppendorf tubes with a volume of 500 μ L were used as the sample containers 50. Time of concentration was recorded when the slush bath was poured into the thermostat 11.

Fig 3 is a schematic diagram illustrating the changes of the sample solutions in the sample containers 50 during freeze concentration (Fig. 3A, 3B, and 3C show the changes at 1, 5 and 7 minutes after the slush bath was added into the thermostat 11. Fig 3D shows the final stage when the ice and the wires 20 were separated from the concentrated solutions remaining in the sample containers 50.). From Fig. 3, it can be seen that the ice came out first on the wires 50 and then spread into other areas of the solutions. With the anions continuously rejected from the ice front, they were concentrated in the remaining solutions. The whole process was finished in 8 minutes. Fig. 4A shows the electropherogram of the sample before concentration. Fig. 4B shows the electropherogram obtained after applying

the freeze concentration process of the present invention. It can be seen that nearly 15 times concentration was obtained.

EXAMPLE 2

One of the advantages of freeze concenntration is that it can be used to concentrate volatile and semi-volatile substances in aqueous solutions. In this example, two phenols (phenol and 3-chloro-phenol, at the concentration of 5 μ g/ml each) were concentrated by the device of the present invention. The conditions used were the same as those in the example 1. Fig. 5A shows the electropherogram of the samples before concentration. Fig. 5B shows the electropherogram obtained after applying the freeze concentration process of the present invention. It can be seen that nearly 8 times concentration was obtained.

EXAMPLE 3

10

15

20

Many biological molecules, such as proteins and RNA, could be damaged during high temperature or organic solvents treatments. Freeze concentration can be a good choice for concentrating such thermally labile and chemically sensitive biological molecules because it doesn't involve any high temperature or organic solvents. This example demonstrates concentrating two proteins (Lysozyme and Trypsin, at the concentration of 12.5 $\mu g/mL$ and 17.5 µg/mL, respectively) using the device of the present invention. First the concentration of the protein solution by the conditions in the examples 1 and 2 was tested. Small concentration efficiency (about 1.5 times) was obtained. The reason may be due to the low diffusion coefficient of the proteins. The growth rate of the ice in the above conditions was significantly faster and may be larger than the diffusion rate of the proteins. Therefore, much of the protein molecules were included into the ice lattice. As such, the growth rate of the ice during freeze concentration was lowered. After using a slush bath (prepared by mixing ethanlene glycol with dry ice) with a temperature - 15 °C as the thermostat 11, nearly 100% recovery for both proteins was obtained. Fig. 6A shows the electropherogram of the samples before concentration. Fig. 6B shows the electropherogram obtained after applying the freeze concentration process of the present invention. It can be seen that nearly 12 times concentration was obtained.

EXAMPLE 4

10

15

20

25

This example illustrates that the present invention may be used to analyze real samples which are considered to be difficult by the current concentration methods. Methanol, ethanol and acetone are widely used raw materials because they are good solvents for many chemicals. Their concentrations in industrial wastewater and surface water have been increasing with the development of chemical industries. It is important to know their concentrations in wastewater in order to control these contaminants. Usually their concentrations need to be below 1 ppm after treatment of the wastewater. Because they are quite hydrophilic, solid phase extraction does not work well in this case. Suitable solvents have also not been found to extract them. However, it is quite easy to concentrate them using the present invention. In a particular example, a wastewater taken from a chemical company was filtered first through a 0.4 μm nylon membrane to remove solids in the solution. After filtration, 0.5 ml solution was filled into the Eppendorf tube in order to apply freeze concentration. Other conditions for freeze concentration were the same as that in example 1. The concentrated solution after concentration was injected directly into a GC instrument (HP series 5890 plus) to measure the concentration of acetone, ethanol and methanol. FIG. 7B shows the results after concentration using the present invention. FIG. 7A is the chromatograph of the solution after filtration. It can be seen from FIG. 7 that the present invention can be used directly to preconcentrate trace amounts of methanol, ethanol and acetone in wastewater for their analysis.

The foregoing description of specific embodiments of this invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be defined by the claims appended hereto and their equivalents.

References

Patent Documents

- 1) SU 1228015 30/04/1986 Dmitrichen M. M.
- 2) BE 794743 / US 3897409 29/07/1975 Bayer AG

5 Other Publications

- 1) Z. Zhou, E. Zheng, and D. Feng, "Determination of trace amount of organic solvent in water by freezing precencentration gas chromatography", Nanjing Huagong Xueyuan Xuebao, Vol. 16, No. 1 (Jan. 1994), pp. 67-71.
- 2) V. V. Aliseichik, A. B. Blank and L. V. Vasetskaya, "Determination of anion impurities in high-purity water by ion chromatography with crystallization preconcentration", Khim. Tekhnol. Vody, Vol. 14, No. 9 (Sept. 1992), pp. 674-712.

Claims

5

10

15

20

25

1. A device for concentrating a plurality of samples comprising:

a first temperature control means having a plurality of container means for containing said plurality of samples;

a second complimentary temperature control means having a plurality of conducting means which are adapted to be inserted in respective samples in said plurality of container means; and

insulating means for insulating said first temperature control means from said second temperature control means such that an amount of heat from said plurality of samples is dissipated through said plurality of conducting means.

- 2. A device according to claim 1, wherein said first and second temperature control means comprise first and second cooling means.
- 3. A device according to claim 2, wherein each of said first cooling means and said second cooling means comprises thermostat controlled cooling means for providing a constant temperature, a stable variable temperature, a temperature gradient, or a series of temperature gradients.
- 4. A device according to claim 1, wherein said plurality of container means are located in a face of said first temperature control means and wherein said insulating means comprises a layer of insulating material disposed on a face of said second temperature control means opposing said face of said first temperature control means, said plurality of conducting means passing from said second temperature control means through said insulating material and, in use, into said plurality of samples in said plurality of container means.
- 5. A device according to claim 1, wherein said insulating means partly or completely prevents transfer of heat between said first temperature control means and said second temperature control means.
- 6. A device according to claim 1, wherein said insulating means comprises a plastic foam insulator.
- 7. A device according to claim 1, wherein said plurality of conducting means comprises

a plurality of wires.

- 8. A device according to claim 7, wherein said plurality of wires are formed from metal, polymer, inorganic or organic material.
- 9. A device according to claim 8, wherein said wires comprise copper wires, each wire optionally comprising an outer protective layer.
 - 10. A device according to claim 7, wherein each of said wires has a diameter of from about several nanometers to several centimeters.
 - 11. A device according to claim 10, wherein said each of said wires has a diameter of about 1mm.
- 10 12. A device according to claim 1, wherein said container means comprises a plurality of wells each of which receives one of said plurality of samples or is adapted to receive a sample container holding one of said plurality of samples.
 - 13. A device according to claim 12, wherein each sample container comprises a tube, bottle or vile.
- 15 14. A device according to claim 13, wherein each sample container comprises a dialysis tube.
 - 15. A device according to claim 1, wherein said first and second temperature control means are individually selected from circulating heaters and coolers, heating and cooling blocks and slush baths.
- 20 16. A device according to claim 1, wherein said first and/or second temperature control means are manually or automatically moveable from a loading position in which samples are loaded into said container means, to an operative position in which said conducting means are inserted into respective samples.
 - 17. A method for concentrating a plurality of samples comprising:
- placing a plurality of samples in a first temperature control means having a plurality of container means for containing said plurality of samples;

inserting a conducting means into each of said samples, said conducting means being mounted relative to a second complimentary temperature control means;

cooling said plurality of samples by means of said first and second temperature control means to selectively crystallize components of said samples; and removing said crystallized components from said samples.

5

15

- 18. A method according to claim 17, wherein said conducting means conduct heat from said samples and act as a support for nucleation during said crystallization, and facilitate removal of said crystallized components.
- 19. A method according to claim 17, wherein said samples are in the form of aqueous solutions, organic solutions, or solids which can be liquefied under certain conditions.
 - 20. A method according to claim 17, wherein said crystallization is carried out at a temperature of said second temperature control means of from about -70°C to about 0°C.
 - 21. A method according to claim 17, wherein said first temperature control means is set at a temperature at which said plurality of samples would be maintained in a liquid state, and wherein said second temperature control means is set at a temperature at which selected components of said plurality of samples are crystallized out of solution.
 - 22. A method according to claim 21, wherein said first temperature control means is set at a temperature above 0°C and said second temperature control means is set at a temperature below 0°C.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6

PCT/SG99/00117






Fig. 7



INTERNATIONAL SEARCH REPORT

International application No. PCT/SG 99/00117

		FC1/3G 99/001	l <u>/</u>
A. CLAS	SIFICATION OF SUBJECT MATTER		
IPC ⁷ : B 0	1 J 9/04		
According to	International Patent Classification (IPC) or to both na	tional classification and IPC	
	OS SEARCHED cumentation searched (classification system followed	hy alagaification gymbols)	
1 _		by classification symbols)	
IPC": B 0	1 J, G 01 N		
Documentati	on searched other than minimum documentation to the	extent that such documents are included in	n the fields searched
Electronic da	ata base consulted during the international search (nam	e of data base and, where practicable, searc	ch terms used)
	·	•	·
WPIL DA	ATABASE, Derwent Publications Ltd., L	ondon (GB) PAJ Database, EPC	PAJ Database
C. DOCU	MENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropri	riate, of the relevant passages	Relevant to claim No.
A, P	WO 98/51393 A1 (GLAXO GROUP L)	IMITED) 19 November 1998	1-22
	(19.11.98), totality.		
A, P	GB 2336908 A (MERCK & CO INC),	03 November 1999 (03.11.99),	1-22
	figures, claims.	`	
A, P	DE 19739120 A1 (FRIEDRICH-SCHII	•	1-22
	11 March 1999 (11.03.99), fig.1, abstrac	et, claims.	
Α	US 5702672 A (S.H.H. DEWITT), 30 I	December 1997 (30.12.97),	1-22
}	abstract.	,	
l			
			·
Further	documents are listed in the continuation of Box C.	See patent family annex.	
	stegories of cited documents: t defining the general state of the art which is not	"T" later document published after the internat date and not in conflict with the applicatio	
considere	d to be of particular relevance	the principle or theory underlying the inve	ntion
filing date	plication or patent but published on or after the international	"X" document of particular relevance; the claim considered novel or cannot be considered	
	which may throw doubts on priority claim(s) or which is stablish the publication date of another citation or other	when the document is taken alone "Y" document of particular relevance; the clain	med invention cannot be
special re	ason (as specified)	considered to involve an inventive step w	hen the document is
means	t referring to an oral disclosure, use, exhibition or other	being obvious to a person skilled in the ar	t
1 "	published prior to the international filing date but later than by date claimed	"&" document member of the same patent fam	nly
	octual completion of the international search	Date of mailing of the international search	h report
	28 March 2000 (28.03.00)	10 April 2000 (10.	04.00)
Name and m	ailing adress of the ISA/AT	Authorized officer	
Austrian	Patent Office		
1	kt 8-10; A-1014 Vienna	Weniger	
Facsimile No	o. 1/53424/200	Telephone No. 1/53424/341	





INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No. PCT/SG 99/00017

Pat nt document cited in search report				\$	Patent i memb	Publication date	
wo	A1	9851393	19-11-1998	AU	A1	76538/98	08-12-1998
				EP	A1	983110	08-03-2000
				GB	OA_	9709811	09-07-1997
GB	A1	2336908	03-11-1999	GB	A0	9908411	09-06-1999
DE	A1	19739120	11-03-1999			none	
ŪS	A	5702672	30-12-1997	AU	A1	53558/94	09-05-1994
				EP	A1	663856	26-07-1995
				JP	T2	8502482	19-03-1996
				MX	A1	9306219	29-04-1994
				WO	A1	9408711	28-04-1994
				US	A	5324483	28-06-1994
				បទ	B1	5324483	24-09-1996
				US	A	5565173	15-10-1996
				US	A	5567391	22-10-1996
				US	A	5582801	10-12-1996
				us	A	5593642	14-01-1997
				US	A	5612002	18-03-1997
				ซร	A	5714127	03-02-1998
				US	A	5766556	16-06-1998
				US	A	5650418	22-07-1997
				AU	A1	84163/91	07-01-1992
				DE	C0	69109676	14-06-1995
				DE	T2	69109676	08-02-1996
				EP	A1	532706	24-03-1993
				EP	A4	532706	30-06-1993
				EP	B1	532706	10-05-1995
				WO	A1	9119488	26-12-1991
				US	A	5230996	27-07-1993
				US	A	5278189	11-01-1994